

To accompany plans dated.

	Anchor Bolts			Square Pedestal						CIDH						
	D 11		T	Pedestal	Reinforcing			Ноор		D.1	* *	Vertical Reinforcing			Spiral	
Post Type No.	Bolt Circle (mm)	Bolts Total & Dia (mm)	Total Length (mm)	Square one side (mm)			# of bars each face	Bar Size	Pitch (mm)	Pile Dia (mm)	Pile Depth (m)	Total	Bar Size		Bar Size	Pitch (mm)
Ш	610	12-51	1270	1600	16	#32	5	#16	89	1372	4.5	26	#32	1143	#16	89
Ш	610	12-51	1270	1600	16	#32	5	#16	89	1372	4.9	26	#32	1143	#16	89
IV	610	12-51	1270	1600	16	#32	5	#16	89	1372	5.5	26	#32	1143	#16	89
٧	864	14-51	1270	1600	16	#32	5	#16	89	1372	5.8	26	#32	1143	#16	89
VI	864	16-64	1524	1753	16	#36	5	#16	89	1524	6.7	28	#36	1295	#16	89
VII	864	16-64	1524	1753	16	#36	5	#16	89	1524	7.0	28	#36	1295	#16	89
VIII	864	16-64	1524	1753	16	#36	5	#16	89	1524	7.6	28	#36	1295	#16	89
IX	864	16-64	1524	1753	16	#36	5	#16	89	1524	7.6	28	#36	1295	#16	89

* * Use Foundation Depth shown in table unless otherwise shown on the Project Plans.

NOTE	۰
------	---

- 1. For anchor bolt layout see post sheet.
- 2. For "Base ${\mathbb R}$ elevation" see Project Plans.
- 3. Prior to erection of the post, backfill which is equivalent to the surrounding material shall be in place.
- 4. Pedestal shall be formed 150 mm minimum below ground surface Remainder to be placed against undisturbed material.
- 5. Slope protection required when indicated on the Project Plans.
- 6. Foundation design is based on 2001 AASHTO article 13.6 Broms' approximate procedure assuming a cohesionless material. The angle of internal friction used is 30 degree and unit weight of soil used is 1922 kg/m³.

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION


OVERHEAD SIGNS-TRUSS SINGLE POST TYPE SQUARE PEDESTAL PILE FOUNDATION

NO SCALE

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN

RSP S7 DATED JANUARY 24, 2005 SUPERSEDES STANDARD PLAN S7 DATED JULY 1, 2004-PAGE 316 OF THE STANDARD PLANS BOOK DATED JULY 2004.

REVISED STANDARD PLAN RSP S7



Pedestal Vert Reinf

#16 ∑ @ 89 mm

0